

## MASKING TAPE



Yellow indoor **DECOR** masking tape from **TM Mustang** is a single-sided adhesive tape made of textured corrugated paper with an adhesive layer of synthetic rubber. Yellow masking tape is one of the consumables that is used in all types of painting and varnishing works. The paper base of the tape is impregnated with a latex compound to enhance water resistance during application. The thickness of the base allows the tape to be removed without tearing, and its density does not allow the masking tape to delaminate and does not allow the edges to rise when paint gets in. The special composition of the rubber adhesive ensures easy removal of the tape after use without glue residues. This type of tape is used for repair and interior decoration work.

| CHARACTERISTICS: | Base<br>material | Adhesive<br>layer   | Vendor<br>code | Size     | Quantity<br>pcs/box | Color  | Heat resistance | Barcode       |
|------------------|------------------|---------------------|----------------|----------|---------------------|--------|-----------------|---------------|
|                  | 01               | 01                  | Q              | K→I      |                     |        | ⇒∥<             | [!!!!!]       |
|                  | Crepe<br>paper   | Synthetic<br>rubber | MY3820         | 38mm*20m | 84 pcs.             | Yellow | to +70°C        | 4824012005701 |
|                  |                  |                     | MY4820         | 48mm*20m | 72 pcs.             |        |                 | 4824012005718 |
|                  |                  |                     | MY4830         | 48mm*30m | 72 pcs.             |        |                 | 4824012005725 |
|                  |                  |                     | MY4850         | 48mm*50m | 36 pcs.             |        |                 | 4824025532942 |

- marking of boundaries when painting with most types of paints;
- temporary fixation, fastening, packaging, sealing and simple masking, where a tape with permanent adhesive is required;
   protection of various elements from the ingress of unwanted
  - substances; • connection of elements for a short period of time;

**APPLICATION:** 

- connection of elements for a short period of time;
  protection of glossy and smooth metal surfaces from damage
- during storage or transportation; • product labeling;
- absence of traces of glue on surfaces after removal;
- density and elasticity of the tape base, combined with
- ADVANTAGES: a high level of strength (resistance to edge tears); • excellent adhesion to various types of surfaces and instant fixation;

- fast marking of drilling points;
- protection of any surfaces (individual sections of walls, tiles, glass, mirrors) when painting, creating multi-color compositions, applying plaster;
- protecting the door leaf from foam during installation;
- protection of glass, plastic and metal surfaces from
- scratches and chips;
- limitation of areas of painting in production and repair work.
- compatibility with most types of paints and varnishes;
- resistance to mechanical impact with abrasive materials;
- ease of tearing, applying and removing the tape;
- flexibility and excellent adhesion to the surface;
- preservation of quality parameters for a long time.