

PROF MOMENT



CHARACTERISTICS:

Base material	Adhesive layer	Vendor code	Size	Quantity in a box	Color	Packaging	Thickness	Heat resistance	Barcode
PET-film	modified acrylic	M095	9mm*5m	30 pcs.	Base - transparent, liner - red	Blister packaging	0,21mm	-40 ... +100°C	4824025532614
		M0155	15mm*5m	30 pcs.					4824025532621

APPLICATION:

PROF MOMENT is ideal for bonding surfaces and materials where instant fixation of objects is required. The thin and transparent base of the tape provides an inconspicuous adhesive contour. It is used for fastening materials to non-polar surfaces: accessories for dashboards, leather, leatherette and car films; for the installation of chrome-plated elements and plastic parts made of plastic in cars. PROF MOMENT is used for the installation of LED strips, cable ducts, electrical boxes, plastic panels, advertising products, decorative elements, lenses and touch panels in electronic devices. The tape has a high level of adhesion to materials: metal, glass, plastic (polyester, polyethylene, polypropylene, ABS, PET), PE and PP films.

ADVANTAGES:

- ultra-high level of initial and final adhesion, provides instant connection of objects and glued surfaces;
- high peel and shear strength;
- high adhesion to materials with high and low surface energy;
- resistance to UV - radiation and moisture;
- transparent and thin base of the tape provides an inconspicuous gluing contour;
- suitable for indoor and outdoor use;
- provides an even and complete structure of the materials to be glued.