



Quality Certificate No. MS5005

Name	ALUMINUM TAPE UNIVERSAL (TM MUSTANG)
Vendor code/ bar-code	ALT505 – 4824012417658 ALT5010 – 4824012014550 ALT5025 – 4824012386411 ALT5040 – 4824012631207
Material	Aluminum foil
Adhesive type	Synthetic rubber
Carrier color	Aluminum
Product parameters	Width 50 mm Length 5, 10, 25, 40 m
Liner	White
Liner material	Siliconized paper
Adhesive strength	20 N/25 mm
Initial adhesion	High
Tape elongation	3%
Tensile strength	52 N/25 mm
Adhesion to steel	7,5 N/25 mm
Temperature range	From -30 to +170°C
Backing thickness	40 μm
Optimum adhesion start time	1 hour
Joint type	Long-time, short-time
UV stability	High
Chemical stability	High
Moisture stability	High
Abrasion resistance	High
Compatibility with materials	Metal, plastic, textile, glass, wood, ceramics
Application environment	Outdoors and indoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

“TECHNICAL ADHESIVE TAPES” Regulations for Production Specification 22.2-39994422-003:2016

Application time – unlimited

The product is not subject to obligatory certification

Person in charge _____

