



Quality Certificate No. MS5034

Name	DOUBLE-SIDED FOAMED TAPE PROF MOUNTING (TM MUSTANG)
Vendor code/ bar-code	PM192 – 4824025532522
Material	Foamed polyethylene
Adhesive type	Acrylic solvent
Carrier color	White
Product parameters	Width 19 mm Length 2 m
Liner	PE film primary
Liner color	Blue
Initial adhesion	Medium
Final adhesion	High
Adhesive strength (N/25 mm)	29 N/25 mm
Backing density	80 kg/m ³
Optimum adhesion start time	24 hours
Elongation	230%
Temperature range	From -20 to +120°C
Backing thickness	1000 μm
Displacement resistance force	5.8 kg/cm ²
Static load resistance force	1000 g/3.23 cm ² within 7 days at +23°C
Joint type	Long-time
Maximum recommended load weight	2.7 kg/25 mm ²
UV stability	High
Resistance to aggressive environment	Medium
Moisture stability	High
Compatibility with materials	Metal, glass, plastic, wood, cardboard, rubber, organic glass, ceramics, stainless steel, polypropylene, polyethylene, polyester, aluminum
Loading level	Medium
Surfaces	Smooth, rugged
Application environment	Indoors and outdoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

“HOUSEHOLD ADHESIVE TAPES” Regulations for Production Specification 22.2-39994422-002:2016

Application time – unlimited

The product is not subject to obligatory certification

Person in charge _____

