

## "UKRPACK HOLDING INDUSTRY" LLC

Address: Ukraine, 02132, Kyiv, Ye. Chavdar St. 2 tel.: (044) 585-21-08 www.uph-tape.com www.mustang-tape.com

Name	DOUBLE-SIDED STICKY TAPE ELECTRO ENERGY FIX (TM MUSTANG )
Vendor code/ bar-code	EL195 - 4824025532805
Material	Foamed polyethylene
Adhesive type	Modified acrylic
Carrier color	White
Product parameters	Width19mmLength5mm
Liner	PE film primary
Liner color	Red
Initial adhesion	High
Final adhesion	High
Adhesive strength ( N/25 mm)	33 N/25 mm
Backing density	93 kg/m <sup>3</sup>
Optimum adhesion start time	24 hours
Elongation	215%
Temperature range	From -20 to +120°C
Backing thickness	1100 μm
Displacement resistance force	$6 \text{ kg/cm}^2$
Static load resistance force	1000 g/3.23 cm <sup>2</sup> within 7 days at $+23^{\circ}$ C
Joint type	Long-time
Maximum recommended load weight	$2.9 \text{ kg}/25 \text{ mm}^2$
UV stability	High
Resistance to aggressive environment	High
Moisture stability	High
Compatibility with materials	Metal, glass, plastic, wood, cardboard, rubber, organic glass, ceramics, stainless steel, polypropylene polyethylene, polyester, aluminum
Loading level	Medium
Surfaces	Smooth, rugged
Application environment	Indoors and outdoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

УКРПАК ХОЛДИНГ ІНДАСТРІ

6

"HOUSEHOLD ADHESIVE TAPES" Regulations for Production Specification 22.2-39994422-002:2016

1084-

Application time – unlimited The product is not subject to obligatory certification

Person in charge