



# “UKRPACK HOLDING INDUSTRY” LLC

Address: Ukraine, 02132, Kyiv, Ye. Chavdar St. 2  
tel.: (044) 585-21-08  
www.uph-tape.com  
www.mustang-tape.com

## Quality Certificate No. MS5030

Name	<b>DOUBLE-SIDED TAPE WITH A POLYPROPYLENE BACKING (TM MUSTANG )</b>
Vendor code/ bar-code	DPP385 – 4824012356551 DPP3810 – 4824012356568 DPP505 – 4824012356575 DPP5010 – 4824012356582 DPP5025 – 4824012126352
Material	Polypropylene film
Adhesive type	Synthetic rubber
Carrier color	Translucent
Product parameters	Width 38, 50 mm Length 5, 10, 25 m
Liner	Siliconized paper
Liner color	Mustard-yellow
Initial adhesion	High
Adhesive strength (N/25 mm)	39 N/25 mm
Adhesion to polypropylene	34 N/25 mm
Adhesion to stainless steel	38,4 N/25 mm
Optimum adhesion start time	24 hours
Shear force	3.9 kgf/cm <sup>2</sup>
Temperature range	From -30 to +90°C
Backing thickness	130 µm
Elongation	74%
Optimum recommended load weight	3.85 kg/25 mm <sup>2</sup>
Joint type	Long-time, short-time
UV stability	Medium
Resistance to aggressive environment	High
Moisture stability	High
Compatibility with materials	Metal, glass, tiles, linoleum, carpeting, wood, laminated cardboard, plastic, PP, PE, painted metal, paper, foils, foam board
Loading level	Medium
Surfaces	Even, smooth
Application environment	Indoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

“TECHNICAL ADHESIVE TAPES” Regulations for Production Specification 22.2-39994422-003:2016

Application time – unlimited

The product is not subject to obligatory certification

Person in charge

