



Quality Certificate No. MS5004

Name	HEAT INSULATING TAPE PROF INSULATION (TM MUSTANG)
Vendor code/ bar-code	TIT5030 – 4824025533413
Material	PVC
Adhesive type	Synthetic rubber
Carrier color	Grey
Product parameters	Width 50 mm Length 30 m
Liner	N/A
Self-extinction capacity	self-extinguishing
Adhesion to steel	6 N/25 mm
Adhesive strength	4 N/25 mm
Dielectric strength	32 V/mm
Initial adhesion	High
Conductivity	maximum 2.5 μ S/cm
Tape elongation	230 %
Tensile strength	128 N/mm
Temperature range	From -10 to +90°C
Backing thickness	125 μ m
Vapor permeability	Relative humidity 30 g/m ² /24 hours at 38°C and 90%
Optimum adhesion start time	12 hours
Joint type	Long-time
UV stability	medium
Chemical stability	low
Moisture stability	High
Compatibility with materials	metal, glass, concrete, ceramics, plastic, rubber, PP, PE, wood
Application environment	Outdoors and indoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

“TECHNICAL ADHESIVE TAPES” Regulations for Production Specification 22.2-39994422-003:2016

Application time – unlimited

The product is not subject to obligatory certification

Person in charge

