



Quality Certificate No. MS5053

Name	REINFORCED TAPE UNIVERSAL GREY (TM MUSTANG)
Vendor code/ bar-code	DT505 – 4824012236112 DT5010 – 4824012425875 DT5025 – 4824012657825 DT5040 – 4824012356919 DT5050 – 4824012854767
Material	PE film + reinforced fabric netting (hot lamination of backing)
Adhesive type	Synthetic rubber
Carrier color	Grey
Product parameters	Width 50 mm Length 5, 10, 25, 40, 50 m
Liner	N/A
Initial adhesion	High
Adhesive strength (N/25 mm)	24 N/25 mm
Tensile strength	89 N/25 mm
Optimum adhesion start time	24 hours
Shear force	2.9 kgf/cm ²
Temperature range	From -30 to +70°C
Backing thickness	180 μm
Elongation	19%
Joint type	Long-time
Elasticity	High
UV stability	Medium
Resistance to aggressive environment	Medium
Moisture stability	High
Compatibility with materials	textile, plastic, glass, ceramics, metal, foils, rubber
Loading level	Medium
Surfaces	Smooth, rugged, even, uneven
Application environment	Indoors and outdoors

Products Quality meets the requirements of the Regulations for Production Specification (industrial standard):

“TECHNICAL ADHESIVE TAPES” Regulations for Production Specification 22.2-39994422-003:2016

Application time – unlimited

The product is not subject to obligatory certification

Person in charge

